

TO-92 NPN Silicon NPN transistor in a TO-92 Plastic Package.

2SA673(A)
Complementary pair with 2SA673(A).

High frequency amplifier.




PIN1 Base PIN 2 Collector PIN 3 Emitter

Parameter	Symbol	Rating	Unit	
Collector to Base Voltage	V_{CBO}	2SC1213	35	V
		2SC1213A	50	
Collector to Emitter Voltage	V_{CEO}	2SC1213	35	V
		2SC1213A	50	
Emitter to Base Voltage	V_{EBO}	4.0	V	
Collector Current - Continuous	I_C	500	mA	
Collector Power Dissipation	P_C	400	mW	
Junction Temperature	T_j	150		
Storage Temperature Range	T_{stg}	-55 150		

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector to Base Breakdown Voltage	V_{CBO}	$I_C=10\mu A$ $I_C=1.0mA$	35			V
			50			
Collector to Emitter Breakdown Voltage	V_{CEO}	$I_C=1.0mA$ $I_B=0$	35			V
			50			
Emitter to Base Breakdown Voltage	V_{EBO}	$I_E=10\mu A$ $I_C=0$	4.0			V
Collector Cut-Off Current	I_{CBO}	$V_{CB}=20V$ $I_E=0$			0.5	μA
DC Current Gain	$h_{FE(1)}$	$V_{CE}=3.0V$ $I_C=10mA$	60		320	
	$h_{FE(2)}$	$V_{CE}=3.0V$ $I_C=500mA$	10			
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=150mA$ $I_B=15mA$		0.2	0.6	V
Base to Emitter Voltage	V_{BE}	$V_{CE}=3.0V$ $I_C=10mA$		0.64		V





BR:

C1213A

B: h_{FE}


Note:

BR: Company Code.

C1213A: Product Type.

B: h_{FE} Classifications Symbol

****: Lot No. Code,code change with Lot No.


Note:

- | | | | |
|---|------------|-----------|---|
| 1 | 25 150 | 60 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 255±5 | 5±0.5sec; | 2.Peak Temp.:255±5 , Duration:5±0.5sec. |
| 3 | 2 10 /sec. | | 3. Cooling Speed: 2~10 /sec. |

270±5

10±1 sec.

Temp:270±5

Time:10±1 sec

/ BULK

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm3)		
	Units/Bag 只/袋	Bags/Inner Box 袋/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Bag 袋	Inner Box 盒	Outer Box 箱
TO-92	1,000	10	10,000	5	50,000	135×190	237×172×102	560×245×195
	1,000	10	10,000	10	100,000	135×190	237×172×102	560×245×375

/ AMMO

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm3)	
	Units/tape 只/纸带	Tape/Inner Box 纸带/盒	Rows/Inner Box 纸带层/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Inner Box 盒	Outer Box 箱
TO-92	3,000	1	120	10	30,000	328×230×42	小箱 480×346×235, 大箱 547×407×268