

/ Descriptions

Silicon NPN transistor in a SOT-89 Plastic Package.


/ Features

Low noise and high gain, large P_C in small package.


/ Applications

low noise amplifier at VHF, UHF and CATV band applications.

/ Equivalent Circuit



/ Pinning



PIN1 Base PIN 2 Collector PIN 3 Emitter

/ Marking

h_{FE} Classifications Symbol	H	F	E	G
h_{FE} Range	50 100	80 160	125 250	200 300
Marking	HRH * *	HRF * *	HRE * *	HRG * *

/ Absolute Maximum Ratings(Ta=25)

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	20	V
Collector to Emitter Voltage	V_{CEO}	12	V
Emitter to Base Voltage	V_{EBO}	3.0	V
Collector Current - Continuous	I_C	100	mA
Collector Power Dissipation	P_C	350	mW
Collector Power Dissipation	* P_C	1.2	W
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55 150	


*:mounted on 16cm²×7mm ceramic substrate.

*:

/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector Cut-Off Current	I_{CBO}	$V_{CB}=10V$ $I_E=0$			1.0	μA
Emitter Base Cut-Off Current	I_{EBO}	$V_{EB}=1.0V$ $I_C=0$			1.0	μA
DC Current Gain	h_{FE}	$V_{CE}=10V$ $I_C=20mA$	50	120	300	
Transition Frequency	f_T	$V_{CE}=10V$ $I_C=20mA$		6.5		GHz
Feed-Back Capacitance	C_{re}	$V_{CB}=10V$ $I_E=0$ $f=1.0MHz$		0.65	1.0	pF
Noise Figure	$NF_{(1)}$	$V_{CE}=10V$ $I_C=7.0mA$ $f=1.0GHz$		1.1		dB
	$NF_{(2)}$	$V_{CE}=10V$ $I_C=40mA$ $f=1.0GHz$		1.8	3.0	dB


/ Electrical Characteristic Curve




/ Package Dimensions

SOT-89

单位: mm



/ Marking Instructions



H
R
H

Note:


H: Company Code.

R: Product Type.

H h_{FE} Classifications Symbol

** : Lot No. Code, code change with Lot No.

() /



Note:

- | | | | | | |
|---|-----|-----|----|----------|---|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 245 | 5 | 5 | 0.5sec; | 2.Peak Temp.:245 5 , Duration:5 0.5sec. |
| 3 | | | 2 | 10 /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260 5 10 1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	只 卷盘	卷盘 盒	只 盒	盒 箱	只 箱	盒	箱	

/ Notices