


Silicon NPN transistor in a TO-92 Plastic Package.

Low current, low voltage.

HF applications in radio and television receivers, FM tuners, low noise AM mixer-oscillators.



PIN 1 Collector PIN 2 Emitter PIN 3 Base



See Marking Instructions.

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	30	V
Collector to Emitter Voltage	V_{CEO}	20	V
Emitter to Base Voltage	V_{EBO}	5.0	V
Collector Current - Continuous	I_C	30	mA
Peak Collector Current	I_{CM}	30	mA
Collector Power Dissipation	P_C	300	mW
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55 150	

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector Cut-Off Current	I_{CBO}	$V_{CB}=20V$ $I_E=0$			0.1	A
Emitter Cut-Off Current	I_{EBO}	$V_{EB}=4.0V$ $I_C=0$			0.04	A


~~DC Current Gain~~

~~h~~



T0-92

Unit: mm





Note:

BR: Company Code.

BF494: Product Type.

****: Lot No. Code,code change with Lot No.



- | | |
|--|---|
| 1 25 150 60 90sec;
2 255 5 5 0.5sec;
3 2 10 /sec. | Note:
1.Preheating:25~150 , Time:60~90sec.
2.Peak Temp.:255 5 , Duration:5 0.5sec.
3. Cooling Speed: 2~10 /sec. |
|--|---|

270 5 10 1 sec. Temp:270±5 Time:10±1 sec

/ BULK

Package Type	Units					Dimension (unit mm3)		
	Units/Bag /	Bags/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Bag	Inner Box	Outer Box
TO-92	1,000	10	10,000	5	50,000	135×190	237×172×102	560×245×195

u23159282