

BRCs020N06SZC

Rev.B Dec.-2024

/ Descriptions

PDFN5×6 N

N-Channel MOSFET in a PDFN5×6 Plastic Package.

/ Features

$V_{DS}(V)=60\text{ V}$ $I_D=158\text{ A}$

$R_{DS(ON)}@10\text{ V } 2.0\text{ m}$ (Typ.1.8mR)

$R_{DS(ON)}@4.5\text{ V } 3.0\text{ m}$ (Typ.2.5mR)


HF Product.

/ Applications


DC-DC

Secondary Side Synchronous Rectification,DC-DC Converter, Motor Control, Load Switching.

/ Equivalent Circuit



/ Pinning



PIN1 2 3 S PIN4 G PIN5 6 7 8 D

/ Marking

See Marking Instructions.

/ Absolute Maximum Ratings($T_a=25$)

Parameter		Symbol	Rating	Unit
Drain-Source Voltage		V_{DS}	60	V
Continuous Drain Current		$I_D(T_c=25)$	158	A
Pulsed Drain Current		I_{DM}	316	A
Gate-Source Voltage		V_{GS}	± 20	V
Power Dissipation		$P_D(T_c=25)$	90	W
Avalanche energy(L=0.5mH)		E_{AS}	380	mJ
Avalanche Current(L=0.5mH)		I_{AS}	30.8	A
Junction and Storage Temperature Range		T_j, T_{stg}	-55 to 150	
Maximum Junction-to-Ambient	t 10s	R_{JA}	20	/ W
	Steady-State		57	
Maximum Junction-to-Case	Steady-State	R_{JC}	1.39	


/ Electrical Characteristics($T_a=25$)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V$ $I_D=250\mu A$	60	65		V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=60V$ $V_{GS}=0V$			1	μA
Gate-Body Leakage Current Forward	I_{GSS}	$V_{GS}=\pm 20V$ $V_{DS}=0V$			± 100	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$ $I_D=250\mu A$	1	1.6	2.5	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V$ $I_D=20A$		1.8	2.5	m
		$V_{GS}=4.5V$ $I_D=10A$		2.4	3.5	
Forward On Voltage	V_{SD}	$V_{GS}=0V$ $I_S=1A$			1.2	V
Gate resistance	R_g	f=1MHz		1.0		
Input Capacitance	C_{iss}	$V_{DS}=25V$ $V_{GS}=0V$ f=1.0MHz		6700		pF
Output Capacitance	C_{oss}			1400		
Reverse Transfer Capacitance	C_{rss}			70		
Total Gate Charge	$Q_{g(10V)}$	$V_{GS}=10V,$ $V_{DS}=30V,$ $I_D=20A$		60		nC
Total Gate Charge	$Q_{g(4.5V)}$			23		
Gate Source Charge	Q_{gs}			16		
Gate Drain Charge	Q_{gd}			3		

/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=10V$ $V_{DS}=20V$ $R_L=1$ $R_{GEN}=3$		13		ns
Turn-On Rise Time	t_r			4		
Turn-Off Delay Time	$t_{d(off)}$			47		
Turn-Off Fall Time	t_f			6.5		

/ Electrical Characteristic Curve



istics **Fig 1: On-Region Characteristics** **Figure 2: Transfer Character**




Figure 3: On-Resistance vs. Drain Current and Gate Voltage **Figure 4**




Figure 5: On-Resistance vs. Gate Voltage **Figure 6: On-Resistance vs. Drain-Source Voltage**

/ Electrical Characteristic Curve






Figure 10: Normalized Maximum Transient Thermal Impedance

/ Package Dimensions

PDFN5 X6


Unit:mm



Rev.01 202209

/ Marking Instructions 8

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- | | | | |
|---|---------|-----------|---|
| 1 | 150 180 | 60 90sec; | 1.Preheating:150~180 , Time:60~90sec. |
| 2 | 245±5 | 5±0.5sec; | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | 2 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel /	Reels/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Reel	Inner Box	Outer Box
PDFN5x6	5,000	2	10,000	6	60,000	13"x12	360x360x50	380x335x366

/ Notices