

BRC5035N03ZC

Rev.A Dec.-2023



DATA SHEET

PDFN5×6 N

N-Channel MOSFET in a PDFN5×6 Plastic Package.

$V_{DS}(V)=30\text{ V}$ $I_D=95\text{ A}$

$R_{DS(ON)}@10\text{ V}$ 3.6m (Typ.3.5mR)

$R_{DS(ON)}@4.5\text{ V}$ 6.5m (Typ.5.0mR)

HF Product.

MB/NB/UMPC/VGA Buck -
Battery Management,High Frequency Point-of-

/ Absolute Maximum Ratings($T_a=25$)

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	30	V
Continuous Drain Current	I_D	95	A
Pulsed Drain Current	I_{DM}	175	A
Gate-Source Voltage	V_{GS}	± 20	V
Power Dissipation	$P_D(T_c=25)$	55	W
Avalanche energy(L=0.5mH)	E_{AS}	281	mJ
Avalanche Current(L=0.5mH)	I_{AS}	26.5	A
Junction and Storage Temperature Range	T_j, T_{stg}	-55 to 150	
Maximum Junction-to-Ambient	t 10s	R_{JA}	/ W
	Steady-State		
Maximum Junction-to-Case	Steady-State	R_{JC}	2.3

/ Electrical Characteristics($T_a=25$)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	BV_{DSS}	$I_D=250\mu A, V_{GS}=0V$	30	33		V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=30V, V_{GS}=0V$			1.0	μA
Gate-Body leakage current	I_{GSS}	$V_{DS}=0V, V_{GS}=\pm 20V$			± 100	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	1	1.7	3.0	V
Static Drain-Source On-Resistance	$R_{DS(ON)}$	$V_{GS}=10V, I_D=20A$		3.5	3.6	m
		$V_{GS}=4.5V, I_D=10A$		5.0	6.5	
Diode Forward Voltage	V_{SD}	$I_S=1A, V_{GS}=0V$			1.4	V
Input Capacitance	C_{iss}	$V_{DS}=25V, V_{GS}=0V, f=1.0MHz$		2200		pF
Output Capacitance	C_{oss}			145		
Reverse Transfer Capacitance	C_{rss}			210		
Gate resistance	R_g	$V_{GS}=0V, V_{DS}=0V, f=1MHz$		2.0		

/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Total Gate Charge	$Q_{g(10V)}$	$V_{GS}=10V$ $V_{DS}=15V$ $I_D=20A$		32		nC
Total Gate Charge	$Q_{g(4.5V)}$			15		
Gate Source Charge	Q_{gs}			5.2		
Gate Drain Charge	Q_{gd}			6.5		
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=10V$ $V_{DS}=15V$ $R_L=0.75$ $R_{GEN}=3$		8.5		ns
Turn-On Rise Time	t_r			4.2		
Turn-Off Delay Time	$t_{d(off)}$			30		
Turn-Off Fall Time	t_f			5.7		

/ Electrical Characteristic Curve







Figure 1: On-Region Characteristics, Figure 2: Transfer Characteristics, Figure 3: On-Resistance vs. Drain Current and Gate Voltage, Figure 4: On-Resistance vs. Junction Temperature, Figure 5: On-Resistance vs. Gate Voltage

/ Electrical Characteristic Curve




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics






Figure 10: Normalized Maximum Transient Thermal Impedance

/ Package Dimensions


PDFN5 X6

Unit:mm



Rev.01 202209

/ Marking Instructions



BR

035N03

Note

BR

Company Code


035N03

Product Type Code

****:

Lot No. Code, code change with Lot No

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------------|-----|----|------------------|--|
| 1 | 150 | 180 | 60 | 90sec; | 1.Preheating:150~180 , Time:60~90sec. |
| 2 | 245 ± 5 | | | 5 ± 0.5 sec; | 2.Peak Temp.: 245 ± 5 , Duration: 5 ± 0.5 sec. |
| 3 | | | 2 | 10 /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260 ± 5 10 ± 1 sec. Temp.: 260 ± 5 Time: 10 ± 1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel /	Reels/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Reel	Inner Box	Outer Box
PDFN5x6	5,000	2	10,000	6	60,000	13"x12	360x360x50	380x335x366

/ Notices