



TO-263 N
N-CHANNEL MOSFET in a TO-263 Plastic Package.

High frequency switching and synchronous rectification,BMS, Motor, Meet the stringent requirements of automotive applications.



PIN 1 G PIN 2 4 D PIN 3 S




See Marking Instructions.

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DSS}	100	V
Drain Current	$I_D(T_C=25^\circ C)$	180	A
Pulsed Drain Current	I_{DM}	385	A
Gate-Source Voltage	V_{GS}	± 20	V
Single Pulsed Avalanche Energy(L=0.5mH)	E_{AS}	563	mJ
Avalanche Current	I_{AS}	37.5	A
Total Power Dissipation	$P_D(T_C=25^\circ C)$	237	W
Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 150	
Thermal Resistance-Junction to Ambient	$t \leq 10s$	R_{JA}	17.7
	Steady-State		70.7
Thermal Resistance-Junction to Case	Steady-State	R_{JC}	0.53

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V$ $I_D=250\mu A$	100	112		V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=100V$ $V_{GS}=0V$			1	μA
Gate-Body Leakage Current Forward	I_{GSS}	$V_{GS}=\pm 20V$ $V_{DS}=0V$			± 100	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$ $I_D=250\mu A$	2	2.9	4	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V$ $I_D=20A$		3.5	4.0	m
Forward On Voltage	V_{SD}	$V_{GS}=0V$ $I_S=1A$			1.2	V
Gate resistance	R_g	$f=1MHz$		1.7		
Input Capacitance	C_{iss}	$V_{DS}=25V$ $V_{GS}=0V$ $f=1MHz$		5550		pF
Output Capacitance	C_{oss}			2050		
Reverse Transfer Capacitance	C_{rss}			180		
Total Gate Charge	$Q_{g(10V)}$	$V_{GS}=10V,$ $V_{DS}=50V,$ $I_D=20A$		80		nC
Gate Source Charge	Q_{gs}			23		
Gate Drain Charge	Q_{gd}			17		



Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=10V$ $V_{DS}=50V$ $R_L=2.5$ $R_{GEN}=3$		25		ns
Turn-On Rise Time	t_r			17		
Turn-Off Delay Time	$t_{d(off)}$			53		
Turn-Off Fall Time	t_f			24		










Figure 11: Normalized Maximum Transient Thermal Impedance



单位: mm

Symbol	Dimensions In Millimeters		Symbol	Dimensions In Millimeter	
	Min	Max		Min	Max
A	4.30	4.70	E	9.00	9.40
B	1.00	1.40			



Q


Note:

BR: Company Code

Q: Automobile halogen-free product Code

035N10SH: Product Type Code

****: Lot No. Code, code change with Lot No

Temperature Profile for IR Reflow Soldering(Pb-Free)


Note:

- | | | | |
|---|---------|------------|---|
| 1 | 150 200 | 60 120sec; | 1.Preheating:150~200 , Time:60~120sec. |
| 2 | 255 5 | 5 0.5sec; | 2.Peak Temp.:255 5 , Duration:5 0.5sec. |
| 3 | 2 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

260 5	10 1 sec.	Temp.:260±5	Time:10±1 sec
-------	-----------	-------------	---------------

/ REEL

Package Type	Units					Dimension (unit mm ³)		
TO-263	800	1	800	6	4,800	13" x24	360x360x50	380x335x366

/ TUBE

Package Type	Units					Dimension (unit mm ³)		
TO-263	50	20	1,000	5	5,000	532x33x7.0	555x164x50	575x290x180