

BRCS1C5P06MAQ

Rev.A Jan.-2025

/ Descriptions

SOT-23 P

P- CHANNEL MOSFET in a SOT-23 Plastic Package.

/ Features

AEC-Q101


Ultra Low on-resistance. fast switching.Low on voltage, Qualified to AEC-Q101 Standards for High Reliability, HF Product.

/ Applications


PWM

PWM application & Load switch, Meet the stringent requirements of automotive applications.

/ Equivalent Circuit



/ Pinning



PIN1 G

PIN 2 S

PIN 3 D

/ Marking

See Marking Instructions.


/ Absolute Maximum Ratings(Ta=25)

Parameter		Symbol	Rating	Unit
Drain-Source Voltage		V_{DSS}	-60	V
Gate-Body Leakage Voltage		V_{GSS}	± 20	V
Drain Current – Continuous		I_D	-2.3	A
Pulsed Drain Current		I_{DM}	-9	A
Power Dissipation		P_D	1.25	W
Operating and Storage Temperature Range		T_J, T_{STG}	-55 150	
Maximum Junction-to-Ambient	t 10s	R_{JA}	72	/W
Maximum Junction-to-Ambient	Steady-State		100	/W
Maximum Junction-to-Lead	Steady-State	R_{JL}	64	/W

/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V$ $I_D=-250$ A	-60	-75		V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$ $I_D=-250$ A	-1	-1.9	-2.5	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=-10V$ $I_D=-2A$		135	150	m
		$V_{GS}=-4.5V$ $I_D=-1A$		160	200	m
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=-60V$ $V_{GS}=0V$			-1.0	A
Gate-Body leakage current	I_{GSS}	$V_{GS}=\pm 20V$ $V_{DS}=0V$			± 100	nA
Drain-Source Diode Forward Voltage	V_{SD}	$V_{GS}=0V$ $I_S=-1A$ $T_J=25$			-1.2	V
Gate resistance	R_g	f=1MHz		6.5		
Input Capacitance	C_{iss}	$V_{DS}=-25V$ $V_{GS}=0V$ f=1.0MHz		800		pF
Output Capacitance	C_{oss}			45		
Reverse Transfer Capacitance	C_{rss}			35		
Total Gate Charge	$Q_{g(-10V)}$	$V_{DS}=-10V$ $V_{GS}=-10.0V$ $I_D=-2A$		12.3		nC
Total Gate Charge	$Q_{g(-4.5V)}$			6.3		
Gate-to-Source Charge	Q_{gs}			1.6		
Gate-to-Drain Charge	Q_{gd}			2.4		
Turn-On Delay Time	$t_{d(on)}$	$V_{DS}=-10V$ $V_{GS}=-10V$ $R_L=5.4$ $R_{GEN}=3$		12		ns
Turn-On Rise Time	t_r			20		
Turn-Off Delay Time	$t_{d(off)}$			20		
Turn-Off Fall Time	t_f			25		

/ Electrical Characteristic Curve



Characteristics

Figure 1: On-Region Characteristics

Figure 2: Transfer Characteristics





Figure 5: On-Resistance vs. Gate-Source Voltage

Figure 6: Body Diode Characteristics

/ Electrical Characteristic Curve




Figure 7: Gate-Charge Characteristics

Figure 8: Capacitance Characteristics






Figure 10: Normalized Maximum Transient Thermal Impedance


/ Package Dimensions

SOT-23

单位: mm



/ Marking Instructions




Q
2P6

Note:

Q: Automobile halogen-free product Code

2P6: Product Type Code

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- 1 150 200 60 120sec; 1.Preheating:150~200 , Time:60~120sec.
- 2 255±5 5±0.5sec; 2.Peak Temp.:255±5 , Duration:5±0.5sec.
- 3 2 10 /sec. 3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units ;>û ;H					Dimension ;>û p . (unit /Æmm³)		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Boxç
SOT-23	3,000	10	30,000	4	120,000	7" x8	210x205x205	445x435x230

/ Notices