

BRES5V0X1B2ZP

Rev.C Aug.-2025

/ Descriptions

DFN1006-2L ESD
DFN1006-2L Plastic Package 1-Line,Bi-directional , ESD Protection Diode.

/ Features

1ns 20KV IEC61000-4-2 4 ESD


Ultra small package, Response Time is Typically < 1 ns, ESD > 20 kV per Human Body Model,IEC61000-4-2 Level 4 ESD Protection,HF Product.

/ Applications


MP3

Suitable for cellular phones audio,MP3 players, Digital cameras, Portable devices, mobile telephone and other users.

/ Equivalent Circuit



/ Pinning



/ Marking


See Marking Instructions.

Parameter	Symbol	Rating	Unit
Peak Pulse Power($t_p = 8/20\mu s$)	P_{PK}	56	W
Peak Pulse Current($t_p = 8/20\mu s$)	I_{PP}	4	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	± 20	KV
ESD according to IEC61000-4-2 contact discharge		± 20	
Junction temperature	T_J	125	
Storage Temperature	T_{STG}	-55~+150	

Definitions of electrical characteristics

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Reverse maximum working voltage	V_{RWM}				5.0	V
Reverse leakage current	I_R	$V_{RWM} = 5.0V$			100	nA
Reverse breakdown voltage ¹⁾		$T_w [RW]-43.4(M)TJ10.45.6.497ri$		\dot{A}		X


/ Electrical Characteristic Curve(Ta=25)



/ Package Dimensions


DFN1006-2L

Unit:mm



Rev.01 202108

/ Marking Instructions




5U

Note

5U Product Type Code

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------|-----|-----------|----------|---|
| 1 | 150 | 180 | 60 | 90sec; | 1.Preheating:150~180 , Time:60~90sec. |
| 2 | 245±5 | | 5±0.5sec; | | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | | | 2 | 10 /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
DFN1006-2L	10,000	10	100,000	6	600,000	7 x8	180x120x180	390x385x205

/ Notices