

/ Descriptions

Silicon NPN transistor in a SOT-89 Plastic Package.

/ Features

Complementary pair with KSA928T.


/ Applications

Audio frequency amplifier applications.

/ Equivalent Circuit



/ Pinning









PIN1 Base PIN 2 Collector PIN 3 Emitter

/ Marking

h_{FE} Classifications Symbol	O	Y
h_{FE} Range	100-200	160-320
Marking	H1O	H1Y

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	30	V
Collector to Emitter Voltage	V_{CEO}	30	V
Emitter to Base Voltage	V		


/ Electrical Characteristic Curve




/ Package Dimensions

SUT-89

单位: mm



/ Marking Instructions



H

1

O: h_{FE}

Note:


H: Company Code.

1: Product Type.

O: h_{FE} Classifications Symbol

** : Lot No. Code, code change with Lot No.

() / K\ d g\ i Xk i \ Gif] \ d] fi @ ' l \] f n ' J f d \ i e ^ Ž G Y \$ = i \ \ ž



Note:

- 1 25 150 60 90sec; 1.Preheating:25~150 , Time:60~90sec.
- 2 245 5 5 0.5sec; 2.Peak Temp.:245 5 , Duration:5 0.5sec.
- 3 2 10 /sec. 3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260 5 10 1 sec. Temp.:260±5°C Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-89	1,000	7	7,000	8	56,000	7" ×12	180×120×180	385×257×392

/ Notices