



TO-277

TO-277 Plastic package Schottky diode.

$$V_F(\text{typ})=0.21\text{V}$$

 High Forward Surge Capability, Ultra Low Forward Voltage Drop $V_F(\text{typ})=0.21\text{V}$, Excellent High Temperature Stability. HF Product.

For use in low voltage,high frequency inverters, free wheeling, and polarity protection applications.




PIN1 Anode PIN 2 Cathode PIN 3 Anode

Suggested Pad layout


See Marking Instructions.


Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage Peak Reverse Voltage	V_{RRM} V_{RWM} V_{RM}	60	V
RMS Reverse voltage	$V_{R(RMS)}$	42	V
Average Rectified Output Current	I_O	20	A
Non-Repetitive Peak Forward Surge Current	I_{FSM}	280	A
Repetitive peak avalanche power	P_{ARM}	30000	W
Junction Temperature Range	$T_{j MAX}$	150	
Storage Temperature Range	T_{stg}	-55~150	
Typical Thermal Resistance	$R_{\theta JA}$ (Note 1)	73	/W


IR - VR



IF - VF







Note:

Product Type.

****:

Lot No. Code, code change with Lot No.

