

## / Descriptions


TO-252          NPN

## / Features

TIP127D

## / Applications

## / Equivalent Circuit



## / h<sub>FE</sub> Classifications & Marking


o

**/ Absolute Maximum Ratings(Ta=25 )**


		~	

**/ Electrical Characteristics(Ta=25 )**



/ Electrical Characteristic Curve



/ Package Dimensions




/ Marking Instructions



BR  
122D  
\*\*\*\*

( ) / Temperature Profile for IR Reflow Soldering(Pb-Free)



± ± ± ±

/ Resistance to Soldering Heat Test Conditions

± ±

/ Packaging SPEC.

封装形式	包装数量					包装尺寸 :		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
TO-252	2,500	2	5,000	5	25,000	13" × 16	360×360×50	385×257×392

封装形式	包装数量					包装尺寸 :		
	Units/Tube 只/套管	Tubes/Inner Box 套管/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Tube 套管	Inner Box 盒	Outer Box 箱
TO-251/252	75	48	3,600	5	18,000	526×20.5×5.25	555×164×50	575×290×180

/ Notices